

HYDROMAX

NEW GEN WPC FLOORING

HYDROMAX 5Gi CLICK FLOORING FOR FLOATING INSTALL

HYDROMAX WPC flooring represents next generation manufacturing techniques utilising sustainable Wood Plastic Composites (WPC) to form a durable, interior waterproof flooring.

The visual décors provide realistic embossed timber textures and colours in both classic and contemporary colour palettes to enhance our modern interiors. The planks also display an attached acoustic foam layer that delivers excellent noise reduction capabilities. HYDROMAX features a robust water based PU coating for everyday scuff resistance.

This next generation Hybrid flooring is dimensionally stable, durable and interior waterproof providing instant appeal for modern housing, retail and commercial shop fitout.

HYDROMAX WPC FLOORING Valinge 5Gi Click 1830 x 228 x 7.6mm						
Colour	Scotia	Trim	Sqm/Ctn	Planks/Ctn	Ctns/Pallet	Micro Bevel
Bronx	Warm Springs	Lugano	2.504m2	6	64	Yes 4 sides
Brooklyn	Buckskin	Sunshine	2.504m2	6	64	Yes 4 sides
Chelsea	Twilight Mist	Rock	2.504m2	6	64	Yes 4 sides
Cooney Island	Barn Oak	Lugano	2.504m2	6	64	Yes 4 sides
Hamptons	Barn Oak	Lugano	2.504m2	6	64	Yes 4 sides
Harlem	Homestead	Brown	2.504m2	6	64	Yes 4 sides
Midtown	Barn Oak	Moon	2.504m2	6	64	Yes 4 sides
Queens	Crystal Lake	Rock	2.504m2	6	64	Yes 4 sides
Soho	Silvermoon	Snow	2.504m2	6	64	Yes 4 sides
Staten Island	Buckskin	Lugano	2.504m2	6	64	Yes 4 sides

Key Features; Interior Waterproof, can be installed in wet areas including bathrooms and laundry. Valinge 5Gi click for easy install. WPC flooring provides a robust surface with good dimensional stability. Excellent for renovations over existing ceramic tiles, minimal telegraphing. High impact surface resistance. Super Width planks. **Attached acoustic underlay to enhance walking comfort, warmth and minimise sound transmission.**

Description & Profile; WPC construction. **Valinge** Patented 5Gi Click. Micro Bevel edges, V4.

Surface features; Embossed realistic timber visuals, colours and textures. Water based PU Matte coating.
VOC Emissions; < E1, **FloorScore Certified** SCS-EC10.3-2014 v3.0.



Preference Floors (SA)

ABN 63 600 454 215
 27 Pambula Street,
 Regency Park SA 5010
t +61 8 8268 8010
f +61 8 8268 8919
e sa@preferencefloors.com.au

Preference Floors (QLD)

ABN 81 169 158 990
 6/268 Evans Road,
 Salisbury QLD 4107
t +61 7 3875 1688
f +61 7 3875 1788
e qld@preferencefloors.com.au

Preference Floors (VIC)

ABN 34 151 422 927
 19 Lanyon Street,
 Dandenong South VIC 3175
t +61 3 9794 5111
f +61 3 9794 5133
e vic@preferencefloors.com.au

Preference Floors (NSW)

ABN 40 117 801 037
 Unit A/31 Sturt Street,
 Smithfield NSW 2164
t +61 2 9738 1188
f +61 2 9738 1199
e sales@preferencefloors.com.au