

ICONIC

ICONIC WPC HYBRID CLICK FLOORING FOR FLOATING INSTALL

ICONIC WPC flooring represents next generation manufacturing techniques utilising sustainable Wood Plastic Composites (WPC) to form a robust, interior waterproof flooring product.

The visual décors provide realistic embossed timber textures and colours in both Australian timber and a classic Oak palette. ICONIC is coated with a scratch resistant water-based PU coating for everyday wear and tear. ICONIC planks also feature an attached acoustic foam layer that delivers excellent noise reduction in-room & for transmission sound between floors.

Our ICONIC next generation WPC flooring is dimensionally stable, exceptionally durable, and interior waterproof. Perfect for modern housing, retail, and commercial fit-out.

ICONIC WPC FLOORING Click 1520 x 228 & 180 x7.5mm

Colour	Scotia	Trim	Sqm/Ctn	Planks/Ctn	Ctns/Pallet	Micro Bevel
Alabaster 228mm	Barn Oak	Lugarno	2.080	6	76	Yes 4 sides
Crystal 228 mm	Pale Gorge	Lugarno	2.080	6	76	Yes 4 sides
Flagstone 228mm		Lugarno	2.080	6	76	Yes 4 sides
Graphite 228mm	Crystal Lake	Rock	2.080	6	76	Yes 4 sides
Jasper 228 mm	Barn Oak	Lugarno	2.080	6	76	Yes 4 sides
Limestone 228mm	Coastal Blackbutt	Lugarno	2.080	6	76	Yes 4 sides
Millstone 228mm	Homestead	Teak	2.080	6	76	Yes 4 sides
Onyx 228mm		Black	2.080	6	76	Yes 4 sides
Pearl Shell 228mm	Crystal Lake	Snow	2.080	6	76	Yes 4 sides
Red Rock 228mm	Warm Springs	Lugarno	2.080	6	76	Yes 4 sides
Smokey Quartz 228mm	Crystal Lake	Moon	2.080	6	76	Yes 4 sides
Tumble Stone 228mm	Crystal Lake	Snow	2.080	6	76	Yes 4 sides
Blackbutt 180mm	Coastal Blackbutt	Blackbutt	2.189	8	70	Yes 4 sides
Spotted Gum 180mm	NSW Spotted Gum	Spotted Gum	2.189	8	70	Yes 4 sides

Key Features: Interior Waterproof, can be installed in wet areas including bathrooms and laundry. Click profile for easy install. WPC flooring provides good dimensional stability with smart looking visual décors. Excellent for renovations over existing ceramic tiles, minimal telegraphing. Excellent installed acoustic performance. Super Width planks, 228mm for Oak and 180mm for Australian Timber décors. **Acoustic test rated, 43 L'nT,w - AAAC 5 Star.**

Acoustic: Attached 1.5mm acoustic underlay to enhance walking comfort and minimise impact & transmission sound.

Description & Profile: WPC construction. Patented Click profile. Micro Bevel edges, V4.

Surface features: Realistic timber visuals, colours, and textures. Water based PU Matte coating.

Slip Rating: AS 4586:2013 Appendix A, Wet Pendulum P3 & Oil-Wet Ramp R10.

Fire Test: CHF Value 9.6Kw/m². Smoke Value 304% min. **VOC Emissions;** < E1, **FloorScore Certified** SCS-EC10.3-2014 v3.0.

© Preference Floors. Head Office 02 97381188.

"The preferred choice"

Homemirus Pty Ltd trading as


Preference
FLOORS