

Specification Sheet

VerduraX Strand Woven Bamboo engineered with a cross laminated (plywood) substrate **1850 x 142 x 14/3 mm**.

VerduraX is an exciting addition to our popular strand woven bamboo range. This new range combines the unique hardness characteristics of Verdura strand woven bamboo as its wear layer, the wear layer is then high pressure bonded onto a stable plywood base. The Plywood substrate is cross laminated to provide excellent dimensional accuracy in both its radial and linear directions; this is an absolute plus for engineered flooring. Plywood is one of the World's most reliable building materials and when combined with Verdura strand woven bamboo we have created a highly attractive flooring product, stable and ideally suited to our demanding Australian climatic conditions and residential floorplans.

The VerduraX is manufactured from sustainable natural resources combining a 3 mm strand woven bamboo wear layer permanently bonded onto an 11 mm hardwood plywood substrate. This trusted method of construction provides a long wearing, stable and durable floor with a finished thickness of 14mm. Perfectly suited for residential, multi-residential and commercial applications.

VerduraX collection is now available in six contemporary colours pre-finished with smooth surfaces for our Natural tones and a rustic surface to complement our contemporary visuals. The collection will provide warmth and natural character to almost any interior.

Quick and easy to lay - no dust, no smell and no mess.

VerduraX Engineered Strand Woven Bamboo plywood substrate 1850 x 142 x 14/3 mm						
Colour	Surface	Scotia	Trim	Pcs /ctn	Sqm/ctn - Ctns/Pal	Micro Bevel
Australiana	Smooth	Coffee	Coffee	6	1.576 - 66	Yes 4 sides
Coffee	Smooth	Coffee	Coffee	6	1.576 - 66	Yes 4 sides
Ghost Gum	Rustic	Silver	Silver	6	1.576 - 66	Yes 4 Sides
Outback	Rustic	Teak	Teak	6	1.576 - 66	Yes 4 sides
Rustic	Rustic	Teak	Teak	6	1.576 - 66	Yes 4 sides
Sandy	Smooth	Oak	Oak	6	1.576 - 66	Yes 4 sides

Key Features; engineered to exacting standards. Manufactured from environmentally certified resource. Extremely stable with excellent wear resistance, reduced expansion and contraction when compared with solid strand woven bamboo. Wear layer can be refurbished and rejuvenated if required.

Installation; the product is manufactured with a Unilin Click profile for a floating installation using a quality 2 or 3 mm undelay incorporating a >75 SD moisture barrier (PE film). Flooring substrate should be flat and dry, (3mm over a 3m radius). Ideally concrete slabs should be coated with a quality Sika, Mapei or similar moisture barrier to provide increased insurance against water or moisture ingress.

Description; Engineered Strand Woven Bamboo permanently bonded to a cross laminated plywood substrate. Unilin click profile.

Grade & Surface; both smooth and rustic face. Product can contain natural characteristics such as under coating surface checking, natural bamboo colour variation, dark culm spots and visual defects that are filled to compliment surface character. Pre-finished, PU Matte coating, and light wire brush to achieve rustic surface

Size & Length; 1850mm length, 142mm width & 14mm thickness with a 3mm Strand Woven Bamboo Wear Layer.

Profile; Unilin Click for floating installation. Micro Bevelled Edges.

Slip Resistance; in accordance with AS/NZS 4586 2013 **R10**. **VOC Emissions;** < **E1**, (Below World Health Organisation Levels)

Fire Test Data; Test Method AS/ISO9239.1.Critical Radiant Flux, kW/m2. 6.7 kW/m2. Mean Smoke Development, 5 percent minutes.

For specification or reseller support contact, www.preferencefloors.com.au

Preference Floors (SA)

ABN 63 600 454 215
27 Pambula Street,
Regency Park SA 5010
t +61 8 8268 8010
f +61 8 8268 8919
e sa@preferencefloors.com.au

Preference Floors (QLD)

ABN 81 169 158 990
6/268 Evans Road,
Salisbury QLD 4107
t +61 7 3875 1688
f +61 7 3875 1788
e qld@preferencefloors.com.au

Preference Floors (VIC)

ABN 34 151 422 927
19 Lanyon Street,
Dandenong South VIC 3175
t +61 3 9794 5111
f +61 3 9794 5133
e vic@preferencefloors.com.au

Preference Floors (NSW)

ABN 40 117 801 037
Unit A/31 Sturt Street,
Smithfield NSW 2164
t +61 2 9738 1188
f +61 2 9738 1199
e sales@preferencefloors.com.au